



Through Mount Cable Assembly


1



2




3




4

ADJUST CABLE LENGTH




5

TURN THE ARM BACK OVER AND ROUTE
CHARGING CABLE OUT OF THE ARM
OR THROUGH THE WALL




6

INSTALL THE ARM ONTO THE WALL USING
M5 X 40mm PHILLIPS PAN HEAD SCREWS (PROVIDED)
TOP SCREW FIRST AND THEN THE BOTTOM SCREW
AND THEN PLACE SCREW CAPS




NOTE: WALL MOUNTING TO STUDS OR CONCRETE WALL


7 ROUTE CHARGING CABLE INTO THE ENCLOSURE OR UNIVERSAL VESA MOUNT. INSTALL ENCLOSURE/VESA MOUNT TO THE ARM USING M4 X 8mm PHILLIPS PAN HEAD SCREWS (PROVIDED)



8 ATTACH CHARGING CABLE TO TABLET, LEAVING A SMALL LOOP OF CABLE BENEATH THE TABLET





9 INSTALL THE ENCLOSURE TOP PLATE/VESA MOUNT PER THEIR INSTRUCTIONS



Tilt Tension Adjustments

ADJUST HINGE TENSION USING WRENCH (PROVIDED)



IN THE BOX




T25 TORX L-Wrench



Cable Management Brackets



Rubber Screw Caps




M5 X 40mm
Phillips Pan Head
Screws



M4 X 8mm
Phillips Pan Head
Screws




M4 X 8mm
Phillips Flat Head
Screws




Swing Arm


1




Or




2




3




4




5




6



IN THE BOX



Apex Enclosure



Keys